




A-Tech 212 LV Epoxy

1:1 Low Viscosity



A-Tech 212 LV is a two component, 100% solids, low viscosity, moisture insensitive epoxy. The A-Tech 212 family of epoxies features a fast gel time. It meets ASTM C-881. The product exhibits a high modulus of elasticity. It is recommended for use in hairline cracks up to 5/16" wide.

Physical Properties

Viscosity (mixed)		300-500 cps
Pot Life		10-15 min.
Final cure (75% strength)		1-2 days
Tensile Strength	ASTM D-638	8500 psi
Tensile Elongation	ASTM D-638 modified	2-4%
Compressive Strength	ASTM D-695	12,000 psi
Compressive Modulus	ASTM D-695	500,000 psi
Shear Strength	ASTM D-732	5100 psi
Bond Strength	ASTM C-882	2800 psi
Deflection Temp @264 psi	ASTM D-648	126 ⁰ F

Benefits:

- Structurally reinforce concrete
- Fast gel time
- Stops water
- Low viscosity for tight cracks

Use in conjunction with Applied Technologies Surface Pastes, Injection Ports and Static Mixers.

Size: 300cc x 3000cc (1:1)
6/Box

Where to Use:

- Cracked concrete
- Delaminated concrete

Use with 1/4" x 32 element static mixer

www.appliedtechnologies.com