

# **ATECH DRY**

## **WATER CUT-OFF POLYURETHANE FOAM**

ATECH DRY is a two component nonflammable, VOC compliant hydrophilic polyurethane injected into nonstructural cracks to prevent water from entering. When mixed no additional water is needed. Used to stop leaks that have excessive amounts of water entering.

### **ADVANTAGES:**

- Easy to apply-1: 1 ratio
- Dual cartridge-USE ONLY WHAT YOU NEED
- Low shrinkage
- Water activated
- Hydrophilic-can incorporate large amounts of water in its structure
- VOC compliant
- Nontoxic (no TDI)
- Closed cell
- Permanently flexible

### **WHERE TO USE:**

Use in narrow to wide cracks in:

- Defective concrete (cracked or honeycombed)
- Cold joints
- Pipe intrusions
- Conduit
- Sewers, manholes etc.

### **PHYSICAL DATA:**

Viscosity mixed	300 cps
Tensile strength (ASTM D 3574-86)	380 psi
Tensile elongation (ASTM D 3574-88)	400%
Bonding strength	150-300 psi
Shrinkage	<10%
Expansion	2-20 times

The logo for Applied Technologies LLC features the word "Applied" in a large, stylized, cursive font. Below it, the words "technologies llc" are written in a smaller, lowercase, sans-serif font.

P. O Box 18476 Fairfield, OH 45018  
1-877-APPLY-IT Fax: (513) 939-3787