

Membrane Mastic

Description

Membrane Mastic is a solvent based rubberized bitumen mastic. Once dried the mastic forms a flexible rubber-like membrane that adheres to varying substrates.

Typical Use

Membrane Mastic is used to seal protusions, seams, edges, overlaps and to detail penetrations. It is used in conjunction with spray applied waterproofing membranes, air barriers and flashing membranes.

Technical Data

Color	Black
Weight	10.6 lbs/gallon
Viscosity	>4000 poise
VOC Content	<200 grams/liter
Flash Point	110° F

Packaging

Membrane Mastic: 2 gallon pails

Warranty

Applied Technologies warrants that the product is free of manufacturing defects and conforms to published specifications in force on the date of acceptance by "the company" of the order. Applied Technologies shall only be held liable under this warranty if the material has been stored, used and applied in accordance with Applied's instructions in the products technical data sheet.

If Applied Technologies, in its sole discretion determines that the product breached the above warranty it will in its sole discretion replace the non-conforming product, refund the purchase price or issue a credit to the buyer of the product. The dollar value of Applied's liability and the buyer's remedy under this limited warranty shall not exceed the purchase price of the material in question. This is the only warranty extended by Applied. There are no other warranties including implied warranties of merchantability and fitness for a particular use and purpose. Applied specifically disclaims liability for any incidental, consequential or other damages including but not limited to, loss of profits or damages to a structure or its contents.

THE FOREGOING WARRANTY SHALL BE EXCLUSIVELY AND IN LIEU OF AN OTHER WARRANTY, EXPRESS OR IMPLIED INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE AND PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OR DEALING, CUSTOM, TRADE OR OTHERWISE

