

ATECH T-DRY

WATER CUT-OFF POLYURETHANE FOAM

ATECH T-DRY is a two component hydrophilic, nonflammable, VOC compliant polyurethane injection resin designed to stop water penetration in nonstructural cracks. When mixed, no additional water is needed and foams within 30 seconds of passing through a static mixer.

ADVANTAGES:

- ULTRA-LOW viscosity
- Dual cartridges-use only what you need
- Easy to apply-1:1 or 2:1 ratios available
- Low shrinkage
- Water activated
- Hydrophilic: can incorporate large amounts of water in its structure
- Safe for potable water
- Nontoxic (no TDI)
- Permanently flexible
- Economical: only one cartridge per 8 ft. crack
- Cured product is inert

WHERE TO USE:

- Defective concrete (cracked or honeycombed)
- Cold joints
- Pipe intrusions
- Conduit
- Sewers, manholes etc.

PHYSICAL DATA:

| | |
|-------------------------------------|-------------|
| Viscosity mixed | 100 cps |
| Tensile elongation (ASTM D 3574-88) | 400% |
| Tensile strength (ASTM D 3574-86) | 380 psi |
| Bonding Strength | 150-300 psi |
| Shrinkage | <5% |
| Expansion | 2-20 times |

applied
technologies llc

P O Box 18476 Fairfield, OH 45018
1-877-APPLY-IT Fax: (513) 939-3787