

Acricoat WB

I. Where to Use

- A. Acricoat WB can be used as a curing compound or concrete sealer on concrete. After drying Acricoat WB forms a protective film. Acricoat WB enhances the color and gives a medium gloss finish.

II. Site Conditions

- A. Substrate surfaces must be clean and free of standing water, dust, dirt, loose material, frost, ice, and snow.
 - a. **Curing:** Apply to fresh concrete after all bleed water has dissipated and application will not mar the surface.
 - b. **Sealing:** Clean concrete surface with detergent and high pressure water to remove any dirt, grease, curing or sealing membranes, paint or any other materials that may prevent adhesion.

III. Application of Acricoat WB

- A. Use a low nap roller or low pressure airless sprayer.
- B. Stir before use.
- C. Do not dilute.
- D. **Curing:** Apply at a rate of 300-400 sq. ft./gallon 7-10 sq. m./L. Apply second coat after first has dried to the touch at right angles to the first. Do not allow ponding. Apply at surface temperatures above 50 degrees F.
- E. **Sealing in Place Concrete: 1st Coat-** Apply at a rate of 300-400 sq. ft./gallon 7-10 sq. m./L. Do not allow ponding. Apply at surface temperatures above 50 degrees F. **2nd Coat-** Apply at a rate of 400-600 sq. ft./gallon 7-10 sq. m./L. Apply second coat after first has dried to the touch at right angles to the first. Do not allow ponding. Apply at surface temperatures above 50 degrees F.
- F. All surfaces should be covered thoroughly
- G. Avoid application in strong winds over 15 mph
- H. Protect glass and metal from coverage. Remove overspray on metal and glass immediately with soap and water.

IV. Safety

- A. Review the Material Safety Data Sheet (MSDS) for complete safety information
- B. Wear goggles or approved safety glasses to protect eyes from misting of the membrane. If contact with eyes happens, flush the eyes with water. If irritation persists, seek medical attention.

V. Equipment Clean Up

- A. Clean pumps and lines with soap and water before drying.

VI. Maintenance

- A. Surfaces previously sealed with Acricoat WB should be cleaned and resealed every 2-5 years, depending on exposure and traffic.

VII. Storage

- A. Do not allow to freeze. Store in sealed containers in cool and dry areas. Shelf life is two years from the date of manufacture.